








MotionBlox40L/60L 4/6 Axis Integrated Motion Controller and Amplifiers

-  Human-Machine Interface
-  Application Code
-  Servo Loop
-  Servo Board
-  Amplifier



INTRODUCTION

The MotionBlox40L/60L plugs straight into the servomotors. It includes 4 or 6 amplifiers, the motion controller as well as the application code. The MotionBlox40L/60L offers the highest level of **integration** and **therefore the lowest cost per axis**.

Multiple MotionBlox40L/60L, Adept Technology robots as well as any other Cerebellum Automation product can be combined on a same FireWire network to add more axes and extra features.

Open Architecture FireWire, Modbus, Profibus-DP, DeviceNet, CAN-Open, Interbus-S, AS-i.

DESCRIPTION

The MotionBlox40L/60L solution is the global answer to multi-axes motion applications.

- The easy to use Cerebellum Automation Integrated Development Environment running on a PC connected to the MotionBlox40L/60L is used for setup, tuning and diagnostic, but is not mandatory for the application program execution.
- The application code is designed specifically for the target machine from Cerebellum Automation's top notch C libraries. It is **embedded** in the MotionBlox40L/60L and runs on a Real Time Operating System. The standard industrial high-speed bus, FireWire, provides the synchronous communication required for coordinated motion and vision systems. The embedded soft IEC 61131 PLC gives the user the option to manage the automation logic of remote I/O.
- The servo loop can be entirely customized to handle non-linear mechanisms and optimize tracking, accuracy and cycle time.

SPECIFICATIONS

- Drives 3 phase AC brushless motors (up to 750W per motor)
- Absolute or incremental encoder inputs
- PowerPC Processor
- FireWire and 2 ports RS-232 connectivity
- 8 KHz servo loops with PID / Feed Forward
- Digital current loop
- 12 Digital Outputs, 8 Inputs (ext. to 44/40 on board and more over Field Bus)
- Embedded IEC 61131 PLC (option)
- Category 3 safety ready (ISO 10218, EN954)
- external 2-character display
- Supports FireWire, Modbus (standard) and Profibus-DP, DeviceNet, CAN-Open, Interbus-S, AS-i (options)
- Built-In Software Tool Box for servo tuning, system diagnostic and application program development
- Low Cost Vision with FireWire Cameras
- Dimensions : 127 x 227 x 427 mm

